

## User Guide

### Frequent Use TFR

22001093/20Lt    22001094/205Lt    22001095/1000Lt

<i><b>Application</b></i>	<b>TFR Value, Performance and Versatility</b>
<i><b>Features &amp; Benefits</b></i>	<ul style="list-style-type: none"> <li>• NTA-Free – safer to use</li> <li>• Optimised performance at minimised cost</li> <li>• Biodegradable formulation</li> <li>• Versatile – manual or pressure washer use</li> </ul>
<i><b>Dilution</b></i>	Light Soiling:    2% (50:1) Medium Soiling   3% (30:1) Heavy Soiling    5% (20:1)
<i><b>Equipment Required</b></i>	<ul style="list-style-type: none"> <li>• Pressure washer</li> <li>• Suitable dilution vessel</li> <li>• Bucket/Mop</li> <li>• Water supply</li> </ul>
<i><b>Use Instructions</b></i>	<ol style="list-style-type: none"> <li>1. Rozone Frequent Use TFR may be used hot or cold via a pressure washer. For best results use hot.</li> <li>2. Suitable dilutions are normally established by experience. See guidance above.</li> <li>3. Apply product at low or high pressure working from the bottom upwards. This avoids streaking on cleaned vehicle.</li> <li>4. In hot weather cool paintwork with water before applying chemical. Do not allow the chemical to dry on the surface.</li> <li>5. Rinse with a bucket, hose or pressure washer from the top of the vehicle, rinsing downwards evenly and methodically.</li> </ol>
<i><b>Hints &amp; Tips</b></i>	<p><i>For the very best results, use warm water (&lt;60°C at machine)</i></p> <p><i>To avoid cleaning-streaks, always work from bottom to top of vehicle.</i></p>
<i><b>Precautions</b></i>	<p>Always observe precautions in material safety data sheet,</p> <p>For fresh or damaged paint/livery always check compatibility on an inconspicuous area first.</p>