

User Guide

Heavy Duty Chassis Cleaner/Degreaser

22001111/20Lt 22001112/205Lt 22001113/1000Lt IBC

<i>Application</i>	Heavy Duty Caustic Cleaner for Chassis & Structural Steel and Workshop Floors
<i>Features & Benefits</i>	<ul style="list-style-type: none"> • Powerful alkaline base cuts deep into encased grime • Corrosion inhibited for protection of sensitive metals • Suitable for use in pressure washers and scrubber driers
<i>Dilution</i>	Regular duty 2% (20ml made up to a litre) Heavy Duty 4% (40ml made up to a litre)
<i>Equipment Required</i>	<ul style="list-style-type: none"> • Pressure washer • Scrubber Drier (for floor cleaning)
<i>Use Instructions</i>	<p>Chassis Cleaning</p> <ol style="list-style-type: none"> 1. Ensure all appropriate PPE is available and correctly fitted. 2. Set equipment to deliver desired concentration of product. 3. With vehicle safely parked over cleaning/inspection pit briefly apply detergent to all surfaces before cleaning. Working from front to back. 4. Then return and apply further chemical working over areas carefully, to remove all soiling. Rinse with cold water. <p>Floor Cleaning</p> <ol style="list-style-type: none"> 1. Dilute to desired concentration (See guidance above). 2. Spread working solution on the area to be cleaned and leave for 3 – 5 minutes. 3. Agitate with a brush or scrubber pad for obstinate areas. 4. Then remove spent solution with a scrubber drier or floor squeegee. Rinse with clean water.
<i>Hints & Tips</i>	<i>For best results use hot.</i>
<i>Precautions</i>	<p>Always observe precautions in material safety data sheet.</p> <p>Never apply to surfaces directly overhead.</p> <p>Take care when using on aluminium components as the product will tarnish polished aluminium. Prolonged contact will etch aluminium.</p> <p>Product should never be used in concentrated form. It must be diluted with water for all cleaning purposes.</p>



User Guide

Heavy Duty Chassis Cleaner/Degreaser

22001111/20Lt 22001112/205Lt 22001113/1000Lt IBC