

# User Guide

## RES Derust

22000749/2x5Lt

22000750/20Lt

<b><i>Application</i></b>	<b>Removal of Corrosion, Atmospheric Tarnish &amp; De-Scaler (Hard Water)</b>
<b><i>Features &amp; Benefits</i></b>	<ul style="list-style-type: none"> <li>• Excellent for single stage cleaning and de-rusting</li> <li>• Will remove grease and oil marks during use</li> <li>• Safe on mild and stainless steel</li> </ul>
<b><i>Dilution</i></b>	<p>Light duty: 5% (50ml in 1 litre of water)</p> <p>Heavy Duty: 50% (500ml in 1 litre of water)</p> <p>On occasions this product may be used neat.</p>
<b><i>Equipment Required</i></b>	<ol style="list-style-type: none"> <li>1. Suitable container for immersion</li> <li>2. Soft cloths/suitable abrasive pads</li> <li>3. Polythene sheeting where appropriate</li> </ol>
<b><i>Use Instructions</i></b>	<p>Ensure that excessive grease and oil is removed from the metal before treating.</p> <p><b>Immersion</b></p> <ol style="list-style-type: none"> <li>1. Dilute as required.</li> <li>2. Mix thoroughly.</li> <li>3. Remove and inspect the item periodically until the soiling has been removed.</li> <li>4. Thoroughly rinse treated items with fresh water and dry.</li> <li>5. Treat with RES Protech if component is likely to corrode.</li> </ol> <p><b>Non-Immersion</b></p> <ol style="list-style-type: none"> <li>1. Apply the solution to the affected area using a suitable pad or cloth.</li> <li>2. Agitate until the corrosion has been removed.</li> <li>3. Wipe off excess product with a damp cloth.</li> <li>4. Treat with RES Protech if component is likely to corrode.</li> </ol>
<b><i>Hints &amp; Tips</i></b>	<i>Use cotton bud/swabs for accessing difficult to access recesses</i>
<b><i>Precautions</i></b>	<p><b>Use all PPE advised in MSDS and COSHH Assessment</b></p> <p>Use with caution on aluminium, zinc and brass.</p> <p>Always check compatibility on an inconspicuous area before use.</p>



# User Guide

## RES Derust

22000749/2x5Lt

22000750/20Lt

Avoid contact with any unprotected bearings.

Do not use on tools or spring steel, saw blades, or high-tensile steel