

Technical User Guide RES Smoke Seal

	22000769/10Lt M0170RES
Application	Encapsulation of Smoke, Odours and all Types of Asbestos
Features & Benefits	 Improves flame retardancy: Independently tested to BS476 Part 6 Class 0 (Fire Propagation Index - Escape Routes) Part 7 Class 1(Walls Ceiling)
	Suitable for suppression of all types of asbestos dust
	Dried film is resistant to mould growth and insect attachment
	 Provides a breathable layer suitable for HVCA applications
	 Fast drying (Touch dry 30 - 120 minutes)
	 Coverage: 2.5 – 5.0/m² per coat (depending on surface).
Dilution	Product is supplied ready to use however it can be diluted with 10% water (900ml of product diluted with 100ml of water) to make application easier.
Equipment Required	Polythene sheeting, Stiff brushes or specialist spray equipment
Use Instructions	 Ensure surfaces are thoroughly clean and dust free To Spray this product This product contains over 50% solids. To spray requires a heavy duty sprayer powered by a compressor. Make sure the surface is clear of debris including dust and smoke residue. Ensure an even coating is applied to all areas. Allow time to dry before applying a second coat. Clean application equipment & spillage with cold water Manual Application Apply using a stiff brush with regular, even strokes in a criss-cross fashion to ensure a thorough seal. Clean application equipment and spillage immediately with
Hints & Tips	cold water. Apply above 5°C. Dried film is washable
Precautions	Use all PPE advised in SDS. Rozone recommends users carry out a full COSHH assessment before using the product. Stir the product well before applying.